

SSCP-0008: Worker Guidewire

Revision: C

Argon Location: All Sites

SUMMARY OF SAFETY AND CLINICAL PERFORMANCE

(SSCP) Worker Guidewires DHF-82256/DD-83013

TD-27

For Publication in Eudamed

ROLE	DEPT	NAME / TITLE		
Prepared by	Regulatory Affairs	Nadira Lotus Manager, Post Market Surveillance		

Signature Approval Matrix

This document must be reviewed and approved by all individuals listed below, or their authorized representatives.

ROLE	DEPT	NAME / TITLE
ApprovalClinical AffairsDanyel Carr Sr. Director, Clinical Affairs		· · · · · · · · · · · · · · · · · · ·
Approval Quality Dan Woda Sr. Quality Engineer		
Approval Regulatory Scott Bishop VP, Regulatory Affairs and Quality		

Revision History

Revision	Date	Sections	Revision Description	Change Request #
A	27 Jul 2023	All	Initial release. Separated worker guidewires from SSCP-003.	N/A
В	19 Feb 2024	All	Harmonize the device name and Intended Purpose per the Declaration of Conformity	04435
С	11/01/2024	4.2	Updating BSI approved IFU numbers and revision numbers, there is no content update.	05589

Note: Approvals will be captured via the associated Change Request.



6.

7.

8. 9.

Summary Of Safety and Clinical Performance (SSCP)

SSCP-0008: Worker Guidewire

Revision: C

Argon Location: All Sites

Table	of Contents	
1.	Scope of this Summary of Safety and Clinical Performance (SSCP):	3
1.1.	Device Trade Name:	3
1.2.	Manufacturer Name and Address	3
1.3.	Manufacturer Single Registration Number (SRN)	3
1.4.	Basic UDI-DI	3
1.5.	European Medical Device Nomenclature	3
1.6.	Class of Device	4
1.7.	Year when the first certificate (CE) was issued covering the device:	5
1.8.	Authorized representative name and SRN:	6
1.9.	Notified Body name and single identification number:	6
2.	Intended use of the device	6
2.1.	Intended purpose	
2.2.	Indications and Target Populations	6
2.3.	Contraindications	
3.	Device Description	
3.1.	Description of the device	
3.2.	Previous Variants and their Differences	
3.3.	Accessories, Compatible Devices, and Other Products Used in Combination	
4.1.	Residual Risks and Undesirable Side Effects	
4.2.	Warnings and Precautions	
4.3.	Other relevant aspects of safety, including a summary of any field safety corrective act	
	A including FSN)	
5.	Summary of clinical evaluation and post-market clinical follow-up (PMCF)	
5.1.	Summary of clinical data related to equivalent device, if applicable	
5.2.	Summary of clinical data from conducted investigations of the device before the C	
	ng, if applicable	
5.3.	Summary of clinical data from other sources, if applicable	
5.4.	An overall summary of the clinical performance and safety	
5.5.	Ongoing or planned post-market clinical follow-up.	.27



SSCP-0008: Worker Guidewire

Revision: C

Argon Location: All Sites

Summary of safety and clinical performance

This Summary of Safety and Clinical Performance (SSCP) is intended to provide public access to an updated summary of the main aspects of the safety and clinical performance of the device from 01/01/2017 to 07/31/2022 (Reporting Interval).

The SSCP is not intended to replace the Instructions for Use as the main document to ensure the safe use of the device, nor is it intended to provide diagnostic or therapeutic suggestions to intended users or patients.

The following information is intended for users/healthcare professionals. A supplemental SSCP with information for patients was not established since the Worker Guidewires is not an implantable device for which patients are provided an implant card, nor is the device intended to be used directly by patients.

1. Scope of this Summary of Safety and Clinical Performance (SSCP):

1.1. Device Trade Name: WORKER™ Guidewire (Standard, Amplatz and Bentson) Amplatz Guidewire EMDN Code C0402: Peripheral Vascular Guidewires; C0401 Coronary Artery Guidewires

1.2. Manufacturer Name and Address

The name and address of the manufacturer of the Worker Guidewire and Amplatz Guidewire (Mermaid Medical) is provided in Table 1.2.1

Table 1.2.1 Manufacturer Information

Manufacturer Name	Address of Manufacturer		
Argon Medical Devices, Inc.	1445 Flat Creek Road Athens, Texas 75751, USA		

1.3. Manufacturer Single Registration Number (SRN)

The Manufacturer Single Registration Number (SRN) is SRN: US-MF-000002324

1.4. Basic UDI-DI

The basic Unique Device Identifier (UDI) key is provided in Table 1.6.1.

1.5. European Medical Device Nomenclature

The EMDN Codes associated with these devices are EMDN Code C0402: Peripheral Vascular Guidewires; C0401 Coronary Artery Guidewires.

1.6. Class of Device

The EU device risk classification for the Worker Guidewires and Amplatz Guidewires are listed in Table 1.6.1.

CAQ-QA-025-F1 Rev F: Summary of Safety and Clinical Performance (SSCP)



Summary Of Safety and Clinical Performance (SSCP) SSCP-0008: Worker Guidewire

Revision: C

Argon Location: All Sites

Table 1.6.1 Device Identification Information

Device Name and Description	Product Number	EU Device Class	Basic UDI-DI
WORKER™ Guidewire Standard Straight 0.035"/80cm/3.5cm	110135080	III	08863332700352V
WORKER™ Guidewire Standard Straight 0.035"/150cm/3.5cm	110135150	III	08863332700352V
WORKER™ Guidewire Standard Straight 0.035"/180cm/3.5cm	110135180	III	08863332700352V
WORKER™ Guidewire Standard Straight 0.038"/150cm/3.5cm	110138150	III	08863332700352V
WORKER™ Guidewire Standard J Curve 0.035"/80cm/3.5cm	110535080	III	08863332700342T
WORKER™ Guidewire Standard J Curve 0.035"/150cm/3.5cm	110535150	III	08863332700342T
WORKER TM Guidewire Standard J Curve 0.035"/180cm/3.5cm	110535180	III	08863332700342T
WORKER™ Guidewire Standard J Curve 0.035"/260cm/3.5cm	110535260	III	08863332700342T
WORKER™ Guidewire Standard J Curve 0.038"/150cm/3.5cm	110538150	III	08863332700342T
WORKER™ Guidewire Amplatz Straight 0.035"/90cm/7.5cm	114035090	III	08863332700332R
WORKER™ Guidewire Amplatz Straight 0.035"/150cm/7.5cm	114035150	III	08863332700322R
WORKER TM Guidewire Amplatz Straight 0.035"/180cm/7.5cm	114035180	III	08863332700332R
WORKER TM Guidewire Amplatz Straight 0.035"/260cm/7.5cm	114035260	III	08863332700332R
WORKER TM Guidewire Amplatz Straight 0.035"/80cm/3.5cm	114135080	III	08863332700332R
WORKER TM Guidewire Amplatz Straight 0.035"/150cm/3.5cm	114135150	III	08863332700332R
WORKER TM Guidewire Amplatz Straight 0.035"/180cm/3.5cm	114135180	III	08863332700332R
WORKER TM Guidewire Amplatz Straight 0.035"/260cm/3.5cm	114135260	III	08863332700332R
WORKER™ Guidewire Amplatz J Curve 0.035"/90cm/7.5cm	114235090	III	08863332700322P



SSCP-0008: Worker Guidewire

Revision: C

Argon Location: All Sites

Device Name and Description	Product Number	EU Device Class	Basic UDI-DI	
WORKER™ Guidewire Amplatz J Curve 0.035"/150cm/7.5cm	114235150	III	08863332700322P	
WORKER™ Guidewire Bentson type 0.035"/180cm/15cm	116035180	III	08863332700362X	
Guidewire Amplatz Guidewire Straight 0.035"/80cm/3.5cm (Mermaid Medical)	G61235080	III	08863332700332R	
Guidewire Amplatz Guidewire Straight t 0.035"/150cm/3.5cm (Mermaid Medical)	G61235150	III	08863332700332R	
Guidewire Amplatz Guidewire Straight 0.035"/180cm/3.5cm (Mermaid Medical)	G61235180	III	08863332700332R	
Guidewire Amplatz Guidewire Straight 0.035"/260cm/3.5cm (Mermaid Medical)	G61235260	III	08863332700332R	
Guidewire Amplatz Guidewire Straight 0.035"/90cm/7.5cm (Mermaid Medical)	G61135090	III	08863332700332R	
Guidewire Amplatz Guidewire Straight 0.035"/150cm/7.5cm (Mermaid Medical)	G61135150	III	08863332700332R	
Guidewire Amplatz Guidewire Straight 0.035"/180cm/7.5cm (Mermaid Medical)	G61135180	III	08863332700332R	
Guidewire Amplatz Guidewire Straight 0.035"/260cm/7.5cm (Mermaid Medical)	G61135260	III	08863332700332R	
Guidewire Amplatz Guidewire J-tip 0.035"/90cm/7.5cm (Mermaid Medical)	G61335090	III	08863332700322P	

1.7. Year when the first certificate (CE) was issued covering the device: DD-83013/TD-27 – WORKERTM Guidewire

The Worker Guidewire have been marketed in Europe since 1996. These guidewires were first marketed by PBN Medicals and later by Medical Devices Technologies, Inc. under CE Mark 0120. Argon acquired the product line in 2013. DE certificate number CE 608299 was first issued for the Worker Guidewire as a Class III medical device on March 31, 2014. This certificate was issued by Argon's notified body BSI. The additional certificates have been issued by BSI:

51, 2011. This certificate was issued by raigon's notified body BSI. The additional
certificates have been issued by BSI:
☐ Full Quality Assurance Certificate CE 565719
☐ ISO 13485 Certificate FM 700791
☐ Design Examination Certificate CE 608299
WORKER Guidewire received market clearance by US FDA on December 8th, 2016
under 510(k) K160785.

1.8. Authorized representative name and SRN:

EMERGO EUROPE, B.V. Westervoortsedijk 60 6827 AT Arnhem



SSCP-0008: Worker Guidewire

Revision: C

Argon Location: All Sites

The Netherlands

SRN: NL-AR-000000116

1.9. Notified Body name and single identification number:

BSI Group The Netherlands B.V. Say Building John M. Keynesplein 9 1066 EP Amsterdam

Notified Body Number: 2797

2. Intended use of the device

2.1. Intended purpose.

The Worker and Amplatz Guidewires are intended to facilitate the percutaneous placement of intravascular devices and non-vascular devices during diagnostic and intervention procedures.

2.2. Indications and Target Populations

The Worker Guidewire and Amplatz Guidewire are indicated for use in angiographic procedures to introduce and position catheters and interventional devices within the coronary and peripheral vasculature. Guidewires are also intended to facilitate the percutaneous placement of peripheral intravascular and non-vascular devices during diagnostic and intervention procedures. The guidewires present an indirect benefit to the patient by enabling diagnosis or procedures targeting the heart and the central circulatory system, the peripheral vascular, or non-vascular procedures related to gallbladder or biliary obstruction and percutaneous drainage. The selection of guidewire is based on physician judgement based on the type of procedure being performed.

2.3. Contraindications

There are no known contraindications.

3. Device Description

3.1. Description of the device

The Worker Guidewire and Amplatz Guidewire are made of stainless-steel core with a polytetrafluoroethylene (PTFE) coated stainless steel spring wire that helps reduce friction during procedure. The guidewires are compatible with medical devices with a lumen larger than the diameter size listed on the label and shorter than the labelled length. Physician judgement required to select the appropriate guidewire compatible with other medical devices to be used.



SSCP-0008: Worker Guidewire

Revision: C

Argon Location: All Sites

The devices and components in the Worker Guidewire and Amplatz Guidewire are packaged as sterile, single use devices. The wires are sealed in Tyvek pouches and packaged with an IFU. The devices are sterilized using ethylene oxide (EtO) sterilization.

A biocompatibility assessment has been completed for the Worker Guidewire and Amplatz Guidewire, and biocompatibility testing was performed according to recommendations set forth in the ISO 10993 *Biological Evaluation of Medical Devices* series standards. The tissue contact categorizations for the Worker and Amplatz Guidewires is externally communicating, circulating blood and limited contact duration (\leq 24 hours).

Table 3.1.1: Worker Guidewire Variations

Trade names WORKER Standard		WORKER Amplatz	WORKER Bentson	
		Stainless steel coated with PTFE	Stainless steel coated with PTFE	
Primary purpose Use in facilitating the placement of catheters within the coronary and peripheral vasculature. They are also for use in the placement of non-vascular catheters		Use in facilitating the placement of catheters within the coronary and peripheral vasculature. They are also for use in the placement of non-vascular catheters	Use in facilitating the placement of catheters within the coronary nd peripheral vasculature. They re also for use in the placement of non-vascular catheters	
Diameter	.035"038"	.018"038"	.018"	
Length	80cm - 260cm	80cm - 260cm	180cm	
Tip styles	3.5cm soft tip, 3mm J & 3.5 cm soft tip	3.5cm or 7.5 cm soft tip, 3mm J & 7.5cm soft tip	15cm soft tip	



SSCP-0008: Worker Guidewire

Revision: C

Argon Location: All Sites

Figure 1: Guidewires, Straight and J Tip





Figure 2: Drawing of Straight and J Tip Standard and Bentson Guidewires





SSCP-0008: Worker Guidewire

Revision: C

Argon Location: All Sites

Figure 3: Drawing of Straight and J Tip Amplatz Guidewires




Figure 4: Drawing of Dispenser Hoop with Flush Adapter and Straightener





SSCP-0008: Worker Guidewire

Revision: C

Argon Location: All Sites

3.2. Previous Variants and their Differences

None

3.3. Accessories, Compatible Devices, and Other Products Used in Combination

Worker Guidewire and Amplatz Guidewire are compatible with medical devices with a lumen larger than the diameter size listed on the label and shorter than the labelled length. Physician judgement required to select the appropriate guidewire compatible with other medical devices to be used.

4. Risks and Warnings

4.1. Residual Risks and Undesirable Side Effects

The Argon Risk Management process is conducted in accordance with EN ISO 14971:2019. Individual residual risk summary and assessment was conducted by review of clinical literature on the subject device and state of the art (SOA) in CER-001 Rev E. The search period covered 01 January 2017 to 31 July 2022. Adverse events identified in the literature are presented in the table below.

Table 4.1.-1: Potential Adverse Events for the Worker Guidewires found in literature.

Potential Adverse Events

Potential complications associated with use of the WORKER Guidewire or Amplatz Guidewire include, but are not limited to:

- Vessel Perforation
- Vessel Dissection
- Thrombus/Occlusion
- Myocardial Infarction
- Perforation of non-intended organs
- Tissue damage
- Infection



SSCP-0008: Worker Guidewire

Revision: C

Argon Location: All Sites

Table 4.1.-2: Adverse Events Reported in the Literature

Adverse Event	Worker Guidewire and Amplatz Guidewire	Guidewires n/N (%)
	n/N (%)	1 (7.3)
Peripheral Vascular		
Vessel Perforation	0/24 (0%)	17/3069 (0.6%)
Vessel Dissection	0/24 (0%)	85/3265 (2.6%)
Thrombus/Occlusion	0/24 (0%)	2/289 (0.7%)
Total	0/24 (0%)	104/3561 (2.9%)
Non-Vascular		
Perforation of non-intended organs	0/59 (0%)	42/3203 (1.3%)
Tissue damage	0/59 (0%)	-
Infection	1/59 (1.7%)	93/3203 (2.9%)
Total	1/59 (1.7%)	135/3203 (4.2%)
Coronary		
Vessel Perforation	-	861/20682 (4.2%)
Vessel Dissection	-	39/5054 (0.8%)
Thrombus/Occlusion	-	59/15794 (0.4%)
Myocardial Infarction	-	236/17435 (1.4%)
Total	-	1195/24861 (4.8%)

^{*}Note: All time points are periprocedural

The current knowledge and state of the art in the percutaneous placement of intravascular and non-vascular devices during diagnostic and interventional procedures by ancillary and standard of care guidewire devices. The literature was assessed for information related to the target population, available alternatives, benchmark, and competitor devices to present a state of the art landscape analysis. Performance and safety outcomes with currently available devices were established from the state current knowledge/state of the art in the field and from a review of published literature on competitor devices to define acceptance criteria. The comparison of acceptance criteria to outcomes with the subject devices demonstrates that the Guidewire Families are considered to be within the current state of the art when used as intended.

4.2. Warnings and Precautions

WORKER™ Guidewire (Standard, Amplatz and Bentson) (IFU1100M & Amplatz Guidewire (IFU1300M):

Warnings

This device was designed, tested and manufactured for single use only. Reuse or reprocessing has not been evaluated and may lead to its failure and subsequent patient illness, infection or other injury. Do not reuse, reprocess or re-sterilize this device.

^{**}Note: n= # of occurrence's, N= total sample size for all studies where "n" was observed

ARGON MEDICAL DEVICES

Summary Of Safety and Clinical Performance (SSCP)

SSCP-0008: Worker Guidewire

Revision: C

Argon Location: All Sites

	Inspect the package integrity before use. Do not use if package appears open or if the expiry date has been exceeded. Do not advance the wire against resistance until the cause of the resistance has
	been determined by fluoroscopy. Excess force against resistance may result in damage to guidewire, or catheter, or vessel perforation. Do not excessively torque the guidewire. Do not entrap or over-rotate the distal tip of the guidewire, it can lead to wire
	rupture. Do not excessively bend the guidewire, it may result in wire fracture. Guidewire placement should be monitored during placement and manipulation using fluoroscopic or suitable imaging method. Do not withdraw a guidewire through a needle. Straighten the guidewire in order to withdraw the needle.
Prec	aution
	Twisting or entanglement of the guidewires may occur when more than one wire is being used simultaneously. This can be prevented by carefully isolating and marking the proximal end of the wires.

4.3. Other relevant aspects of safety, including a summary of any field safety corrective action (FSCA including FSN)

There was one recall for WORKERTM Guidewire, Amplatz, straight during the reporting interval. CAPA C-2019-005 was implemented due to this incident (PMSR-0008 Rev D).

Recall Number	Product Description	Trade Name	Recall Class	Center Classificati on DT	Manufacturer Recall Reason
Z-1791-2020	-0.035"(.89mm) x80 cm guidewire. Model 114135080. Soft Tip 3.5cm. REF/UDI: 114135080/(01)208863333008067. RxOnly STERILE EO -0.035"(.89mm) x150 cm guidewire. Model 114135150. Soft Tip 3.5cm. REF/UDI: 114135150/(01)20886333008074. RxOnly.STERILE EO	WORKER TM Guidewire, Amplatz, straight	1	2020/05/07	The stiffness of the soft end of the guidewire caused tissue perforation.

5. Summary of clinical evaluation and post-market clinical follow-up (PMCF)

5.1. Summary of clinical data related to equivalent device, if applicable

Not applicable, as no equivalence is being claimed for Worker guidewire

5.2. Summary of clinical data from conducted investigations of the device before the CE-marking, if applicable

Not applicable. There were no clinical investigations of the Worker Guidewire prior to CE marking.



SSCP-0008: Worker Guidewire

Revision: C

Argon Location: All Sites

5.3. Summary of clinical data from other sources, if applicable

Clinical data supporting the safety and performance of the Worker Guidewire have been derived from the following sources:

- PMCF activities of the Worker Guidewire Families including customer surveys
 - Survey Report Worker Guidewire Product Family (January 2018 to September 2019)
 - Survey Report –Guidewires (01 September 2017 through 01 September 2020)
- ☐ The Medline and EMBASE databases were used for the literature search for the period from 01 January 2017 to 31 July 2022. It contains comprehensive datasets of ongoing clinical investigations, peer reviewed scientific publications, current guidelines and recommendations released by medical associations, as well as the systematic literature reviews conducted to establish these recommendations.

The PMCF activities are documented in the PMCFP-0027 Rev D.

Table 5.3.-1: PMCF Study Summary

Name of the Activity	Description of Activity	Aim of Activity	Rationale and Known Limitations of Activity	Date of Completion/ Estimated Timeline	
Post-Market Clinical Follow Up Survey Report- Argon Guidewires (N=36)	Customer Feedback Surveys Survey from health care professional/user	To capture the feedback on end users' satisfaction regarding a particular product's performance, end users' concerns in a particular product's safety and potential risk, overall user satisfaction regarding the product category and user profile and their chosen of similar products.	The sample size is relatively small for three of the product families evaluated:	18 November 2020	
WORKER GUIDEWIRE PRODUCT FAMILY CUSTOMER SURVEY (N=53)	Customer Feedback Surveys Survey from health care professional/user	To obtain clinicians feedback related to the clinical safety and performance objectives of the Worker Guidewire devices.	The goal is to reach a minimum 85% acceptability/positive feedback from the endusers	September 2019	

Survey Report – Worker Guidewire Product Family

The objective of this survey was to obtain clinicians feedback related to the clinical safety and performance objectives of the Worker Guidewire devices.

The survey was submitted via paper format and online to end-users (physicians/clinicians) of the product line. The research approach was qualitative (yes/no answers) rather than quantitative (e.g., performing a laboratory measurement on a parameter of interest). The relevance of the Yes/No style questions are based on the simplistic nature of each objective. There were 10 questions on the survey that applied to all the Worker guidewire variants. Argon Medical had intended to analyze the survey data after collecting at

ARGON

Summary Of Safety and Clinical Performance (SSCP)

SSCP-0008: Worker Guidewire

Revision: C

Argon Location: All Sites

least 35 surveys; however, more surveys were received, and that data was incorporated. Qualitative analyses require a smaller sample size than the quantitative analyses.

A total of 53 respondents completed the survey. A minimum of 85% acceptability/positive feedback from the end-users was achieved except for Question #3 which was at 81% due to 6 of the 33 responses indicated that, the flexible tip of the Amplatz guidewire did not provide atraumatic navigation within the vessels. All the 6 responses were provided by the clinicians from the same hospital referencing one complaint issue that had just occurred at that facility. There were no new risks or concerns identified.

Survey Report – The Guidewires

The product-specific variants being surveyed are Bentson, Double ended, Movable core, Stainless Steel Fixed Core (SS Fixed Core) and PTFE Fixed Core.

The survey is an end user self-administrated survey conducted via paper form or online interactive format consisted of Yes/No questions and open-ended questions related to patient safety, product quality, as well as the user profile regarding use of other guidewires from other manufacturers. In closing, respondents were asked to provide any other feedback on the products evaluated.

The custom	er f	eedback survey consisted of five domains and was divided into three sections:							
	Ge	Product-Specific Safety and Performance General Satisfaction and User Profile Respondent Information.							
The survey	don	nains are as follows:							
		Product-Specific Safety & Performance. This domain includes product-specific metrics and questions like trackability, torqueability, flexibility, crossability, supportability and tactile feedback. Additional patient safety concerns related to the use of the device General satisfaction regarding the quality of the guidewires General product performance User profile.							

The target survey population was the end users of the guidewires who are clinicians performing vascular procedures using any of the product families within the guidewire product line for its intended uses.

The customer survey was sent to all global end users in various medical institutions through the company's sales network of distributors and direct sales representatives.

A total of 36 surveys were completed by end users who used at least one family of the Guidewires products between 10 September 2020 through 13 November 2020. The end users were radiology technicians (n=6) and physicians (n=30).

The guidewires usage by respondents is shown below in Table 5.3.-2 Error! Reference source not found. A total of 30/36 (83.3%) respondents used one type of guidewires, 5/36 respondents (13.9%) used 2 types of guidewires, and 1/36 respondent (2.8%) used all the guidewire types.



SSCP-0008: Worker Guidewire

Revision: C

Argon Location: All Sites

Table 5.3.-2: Number and Type of Argon Products Used

Manufacturer	Number of Respondents (n=36)	Percent (%)
Single Product	30	83.3
Bentson	13	36.1
PTFE Fixed Core –J-tip	11	30.6
PTFE Fixed Core –Straight -tip1	5	13.9
Double-Ended	1	2.8
Two Products	5	13.9
Bentson, Movable Core	1	2.8
Bentson, PTFE Fixed Core _Jtip	2	5.6
Bentson, SS Fixed Core – J-tip	1	2.8
PTFE Fixed Core –J-tip, SS Fixed Core – J-tip	1	2.8
All Seven Products	1	2.8

The response rate was 100% for all metrics in all families except for trackability (89%) in Bentson family. The customer feedback survey results by product were presented in Table 5.3.-3.

Table 5.3.-3: Customer Feedback Survey Results by Product

Guidewires Type	# of Users	Flexibility	Trackability	Torqueability	Control of Stiffness/ Flexibility	Tactile Feedback	Crossability
Bentson	18	18 (100%)	16 (89%)	N/A	N/A	N/A	N/A
Double- Ended	2	2 (100%)	2 (100%)	2 (100%)	N/A	N/A	N/A
Movable Core	2	N/A	N/A	2 (100%)	2 (100%)	N/A	N/A
PTFE Fixed Core 1	20	2 (100%)	2 (100%)	2 (100%)	N/A	N/A	N/A
SS Fixed Core 2	3	3 (100%)	3 (100%)	3 (100%)	N/A	3 (100%)	2 (100%)

Note: 1. There were 14 PTFE J-Tip users, 5 Straight Tip, and 1 used both. 2. There were 2 SS J-Tip users and 1 used both SS J-tip and Straight Tip. 3. One user did not answer this item.

The overall clinical experience with the guidewires is presented in Table 5.3.-4



SSCP-0008: Worker Guidewire

Revision: C

Argon Location: All Sites

Table 5.3.-4: General Product Satisfaction

Item	Number of Respondents	Yes	No
Additional Safety Concerns	35	1 (3%)	34 (97%)
Product Package Acceptable	36	36 (100%)	0
Overall Quality Acceptable	36	36 (100%)	0
Overall Performance Acceptable ¹	36	35 (97%)	1 (3%)
Product Tolerated by the Patient	28	28 (100%)	
Product Support Introduction and Placement of Interventional Devices Within the Vasculature ¹	35	34 (97%)	1 (3%)
Use Guidewires from a Different Manufacturer	36	33 (92%)	3 (8%)

One user (#001) indicated the overall product performance was not acceptable and responded that the product does not support introduction and placement of interventional devices within the vasculature. The remark for both survey questions is 'shaft is too flexible for sufficient trackability.

A total of 35 respondents indicated that no additional patient safety concerns related to the use of the guidewires, while 1 respondent indicated that the tip of the Bentson guidewire is very stiff, and it could inadvertently puncture a vessel if placed forcefully. A total of 28 (100%) respondents indicated that the products were tolerated by all patients. The overall product quality was acceptable by all 36 (100%) respondents while the product performance was acceptable to 35 (97%) of the 36 respondents. The Guidewires support introduction and placement of interventional devices within the vasculature was supported by 34/36 (97%) respondents. A total of 33 (91.7%) respondents indicated the use of guidewires from Terumo (16/33, 48.5%), Boston Scientific (15/33, 45.5), Merit (7/33, 21.2%), Cook/Cook Medical (6/33, 18.2%) and Abbott (3/33, 9.1%).

A total of 36 respondents (100%) are satisfied with the guidewires with respect to overall product quality, patient tolerability and product packaging; and all except one (97%) of them are satisfied with overall product performance, safety, and product support introduction and placement of interventional devices within the vasculature. There were no new risks or concerns identified.

Appraisal and Data Extraction of Relevant Clinical Literature

A total of 147 subject device articles were identified in the systematic literature search for this initial MDR CER-001 Rev E, and 3 articles met the inclusion criteria. Summary of the clinical data from the 3 included articles are presented below.



SSCP-0008: Worker Guidewire

Revision: C

Argon Location: All Sites

Article 1. Teoh AYB, Serna C, Penas I, et al. Endoscopic ultrasound-guided gallbladder drainage reduces adverse events compared with percutaneous cholecystostomy in patients who are unfit for cholecystectomy. Endoscopy. 2017;49(2):130-138.¹²⁷

Device/Configuration	0.035" Amplatz guidewire (Argon Medical Devices, Inc.)
Application/Indication	ACC, on-label
Anatomical location	Gall bladder
Appraisal	D1 A1 P1 R1 T1 O1 F1 S1 C1
Article Level	1
Subject device /subject device configuration (n)	0.035" Amplatz guidewire (Argon Medical Devices, Inc.) (n=59)
Competitor/other device (n)	NR
CER objective follow-up duration	Periprocedural
CER objectives: Safety	
Tissue Damage	0/59 (0%)
Perforation/puncture (of non-intended organs)	0/59 (0%)
Infection	Sepsis: 1/59 (1.69%) Urinary tract infection: 0/59 (0%)
CER objectives: Performance	
Technical success	59/59 (100%)
Procedural success	56/59 (94.9%)1
New AE or device issues identified	No

¹Considered based on clinical success. However, complications occurred a day after the procedure was performed NR-Not Reported

Objective: To compare endoscopic ultrasound-guided gallbladder drainage (EGBD) with percutaneous cholecystostomy as a definitive management approach for acute cholecystitis in patients who are unfit for surgery.

Patients and Methods: Between November 2011 and August 2014, in a multicenter, retrospective, 1:1 matched cohort study of 118 patients, 59 acute cholecystitis patients (males, n=30; females, n=29) of mean age: 81.2±10.4 years, underwent percutaneous cholecystostomy. The outcomes were matched for age, sex, and American Society of Anaesthesiologists grade.

A 0.035" inch Amplatz guidewire (Argon Medical Devices Inc., USA) was inserted through the needle and securely coiled inside the gallbladder lumen followed by serial tract dilations. Once the tract had been adequately dilated, a suitable size of pigtail drainage catheter was inserted into the gallbladder lumen over the guidewire.



SSCP-0008: Worker Guidewire

Revision: C

Argon Location: All Sites

The outcome measures included the technical and clinical success rates, adverse event rates, hospital stay, the number of unplanned admissions, and mortality. Technical success was defined as the ability to access and drain the gallbladder by placement of a drainage tube or stent with immediate drainage of bile. Clinical success was defined as improvement in clinical symptoms and decreasing white cell counts within 5 days after the procedure.

Results: Technical success was achieved in all patients and clinical success was achieved in 56/59 (94.9%) patients. There were no instances of any tissue damage, perforation/puncture (of non-intended organs), urinary tract infection. One patient (1.69%) experienced severe sepsis that led to acute renal failure and death.

The overall adverse event rate was 44/59, (74.6%). The 30-day adverse events occurred in 10/59 (16.9%) patients and severe adverse events were observed in 44/59, (74.6%) patients. The unplanned admissions related to the intervention were observed in 4 42/59, (71.2%) patients and recurrent acute cholecystitis occurred in 4/59, (6.8%) patients, and no intraprocedural adverse events were encountered, respectively.

Conclusion: The authors concluded that, the percutaneous cholecystostomy technique was an effective means of achieving gallbladder drainage in acute cholecystitis patients unfit for surgery.

Article 2. Yip HK, Youssef AA, Chang WN, et al. Feasibility and safety of transradial arterial approach for simultaneous right and left vertebral artery angiographic studies and stenting. Cardiovasc Intervent Radiol. 2007;30(5):840-846¹²⁸

Device/Configuration	J-tip Teflon guide wire (Argon Medical Devices)				
Application/Indication	Vertebral angiography and stenting/ carotid artery angiography in patients				
	with vertebral artery stenosis/carotid artery stenosis; on-label				
Anatomical location	Circulatory vasculature/peripheral arterial vasculature				
Appraisal	D1 A1 P1 R1 T1 O1 F1 S1 C1				
Article Level	1				
Subject device /subject device configuration	J-tip Teflon guide wire (N=24 patients)				
(n)					
Competitor/other device (n)	NR				
CER objective follow-up duration	Periprocedural				
CER objectives: Safety					
Vessel Perforation	0/24 (0%)				
Vessel Dissection	0/24 (0%)				
Thrombus/Occlusion	0/24 (0%)				
CER objectives: Performance					
Technical success	24/24 (100%)				
Procedural success	24/24 (100%)1				
New AE or device issues identified	No				

¹Considered based on technical success. However, complications occurred a day after the procedure was performed.



SSCP-0008: Worker Guidewire

Revision: C

Argon Location: All Sites

NR; Not Reported

Objective: To study the safety and effectiveness of the transradial artery (TRA) approach using a 6-French (F) Kimny guiding catheter for right VA angiographic study and stenting.

Patients and Methods: This is a prospective study of 24 consecutive patients with VA stenosis/carotid artery stenosis who underwent vertebral and carotid artery angiography followed by VA stenting between November 2004 and December 2006 were included in this study. The baseline characteristics and comorbidities were as follows: mean age: 68.7 ± 9.5 years, males: 22/24 (91.7%), hypertension: 21/24 (87.5%), diabetes mellitus: 11/24 (45.8%), current smoking: 11/24 (45.8%), prior MI: 3/24 (8.3%) and, prior TIA: 10/24 (41.7%). For this VA angiographic study, a combination of the ipsilateral and retrograde-engagement technique, which involved a looping 6-F Kimny guiding catheter along with the 0.035-inch J-tip Teflon guidewire (Argon Medical Devices), was utilized. For VA stenting, an ipsilateral TRA approach with either a Kimny guiding catheter or a left internal mammary artery guiding catheter was utilized in 22 patients and retrograde-engagement technique in 2 patients. A $\geq 50\%$ stenosis in either the carotid artery, the vertebral artery, or the main intracranial artery was defined as a significant obstruction of these vessels. Severe obstruction was defined as $\geq 70\%$ stenosis.

Results: The left TRA approach was used in most cases. Significant coronary artery obstruction was found in 83.3% and significant stenosis of extracranial carotid arteries was found in 33.3% of the study patients. Technical success of the procedure was reported 100% in all patients, including left VA stenting in 15 patients and right VA stenting in 9 patients. Procedure-related neurological complications were reported in 1 patient (4.2%). There were no vascular or wound complications and procedure related deaths reported.

Conclusion: Authors concluded that TRA approach for both cerebral and coronary angiographic studies and VA stenting is safe and effective. In patients unsuited for femoral arterial access, it can be considered as a simple and useful clinical tool.



SSCP-0008: Worker Guidewire

Revision: C

Argon Location: All Sites

Article 3. Alqahtani S, Kandeel AY, Rolf T, Frederic G, Qanadli SD. Case report: an unusual combined retrograde and antegrade transpedal subintimal recanalization of the infrainguinal arteries. J Vasc Interv Radiol. 2012;23(10):1325-1329.

Device/Configuration	POINTER nitinol guide wire (Angiotech Medical Device Technologies)
Application/Indication	Combined retrograde and antegrade transpedal subintimal recanalization of infrainguinal vessels [SFA, popliteal artery, tibioperoneal trunk, peroneal artery]/CLI, on-label
Anatomical location	Infrainguinal vessels (SFA, popliteal artery, tibioperoneal trunk, peroneal artery)
Appraisal	D1 A1 P1 R1 T2 O1 F1 S2 C1
Article Level	1
Subject device /subject device configuration (n)	POINTER nitinol guide wire (N=1 patient)
Competitor/other device (n)	NR
CER objective follow-up duration	Periprocedural
CER objectives: Safety	
Vessel Perforation	NR
Vessel Dissection	NR
Thrombus/Occlusion	NR
CER objectives: Performance	
Technical success	1/1*
Procedural success	1/1
New AE or device issues identified	No

NR; Not Reported

Objective: To describe a novel technique for retrograde recanalization of the infrainguinal arteries, even when no patent arteries can be identified at or below the level of the knee joint.

Patients and Methods: The authors described a case of a 66-year-old male patient with a past medical history of diabetes, ischemic cardiomyopathy, and right hemiplegia. He presented with a 3-month-old nonhealing ulcer of the dorsum of the left foot associated with left foot pain at rest for past 1-month. CT angiography showed complete occlusion of the superficial femoral, popliteal, infrapopliteal arteries and calcified stenosis in the left common femoral artery (CFA) extending into the profunda femoris artery. Endarterectomy with patch angioplasty of the left CFA and profunda femoris was unsuccessful for which, antegrade recanalization was performed and was unsuccessful. Finally, retrograde approach through the left dorsalis pedis artery was performed which resulted in recanalization of the totally occluded anterior tibial, popliteal, and superficial femoral arteries subintimally until CFA was reached.

^{*}Difficulty of pushing guidewire was due to the extensive calcification however, the balloon angioplasty and stenting were performed, and blood flow was restored.



SSCP-0008: Worker Guidewire

Revision: C

Argon Location: All Sites

The 0.014-inch guidewire was exchanged with a 0.018 inch, 300-cm POINTER nitinol guide wire (Angiotech Medical Device Technologies) which was pushed with difficulty into the true lumen of the proximal tibioperoneal trunk due to extensive calcification in the artery. Antegrade balloon angioplasty of the peroneal and tibioperoneal arteries followed by balloon dilatation of popliteal and SFA was performed. Extensive calcification was noted for which two self-expanding stents were deployed into the proximal SFA to upper part of the popliteal artery.

Results: Control angiography revealed recanalization of the SFA, popliteal, tibioperoneal trunk and peroneal arteries with flow restoration to the foot through plantar arch. Pain at rest disappeared immediately after the procedure. Improvement of the distal flow was documented on follow-up ultrasound studies performed on the same day and on the day after the procedure. On day 10, the patient was discharged with aspirin and clopidogrel medication. Complete healing of the ulcer was noted seven weeks post-procedure. At 6-month follow-up visit, the patient remained well, without any presence of pain at rest or a new foot ulcer.

Conclusion: Authors concluded that in selected patients with CLI who have occlusion of all infrapopliteal arteries and are at high surgical risk or in whom a previous antegrade approach has failed, retrograde subintimal recanalization of chronically occluded infrainguinal vessels through an occluded dorsalis pedis artery access is a feasible and useful approach.



Summary Of Safety and Clinical Performance (SSCP) SSCP-0008: Worker Guidewires

Revision: C

Argon Location: All Sites

Table 5.3.-5: Classification, Assessment, and Appraisal of Subject Devices Literature – Peripheral Vascular

Reference	Device	Study Design	Appraisa	Appraisal Criteria for Suitability		Appraisal Criteria for Data Contribution				1	LOE	
Yip et al., 2007 ¹²⁸	J-tip Teflon guide wire (Argon Medical Devices, Inc.) Diameter: 0.035 inches Length: 260 cm	Prospective study November 2004 to December 2006	D1	A1	P1	R1	T2	O1	F1	S1	C1	1
Alqahtani et al., 2012 ¹²⁹	POINTER nitinol guide wire (Angiotech Medical Device Technologies) Diameter: 0.018 inches Length: 300 cm	Case report	D1	A1	P1	R1	T2	O1	F1	S2	C1	1

Note: All time points are periprocedural

Table 5.3.-6: Classification, Assessment, and Appraisal of Subject Devices Literature - Non-Vascular

Reference	Device	Study Design	Appraisal Criteria for Suitability		Appraisal Criteria for Data Contribution				LOE			
Teoh et al., 2016 ¹²⁷	Amplatz Guidewire (Argon Medical Devices, Inc.) Diameter: 0.035 inches	Multi-center, retrospective, cohort study November 2011 and August 2014	D1	A1	P1	R1	T2	O1	F1	S1	C1	1

Note: All time points are periprocedural



SSCP-0008: Worker Guidewires

Revision: C

Argon Location: All Sites

Table 5.3.-7: Rates of Safety and Performance Outcome Measures Reported from Subject Devices Analysis – Peripheral Vascular

	Safety		Performance		
Reference	Vessel Perforation n/N (%)	Vessel Dissection n/N (%)	Thrombus/Occlusion n/N (%)	Technical Success n/N (%)	Procedural Success n/N (%)
Yip et al., 2007 ¹²⁸	0/24 (0%)	0/24 (0%)	0/24 (0%)	24/24 (100%)	24/24 (100%)
Alqahtani et al., 2012 ^{129 a}	NR	NR	NR	1/1	1/1
Overall Range	0%	0%	0%	100%	100%
Acceptance Criteria	Less than 2.4%	Less than 2.9%	Less than 1.9%	Greater than 81.8%	Greater than 83.3%
All Datasets Meet Acceptance Criteria (Yes/No)	Yes	Yes	Yes	Yes	Yes

^a As this a case report, the article was not considered for overall range as we do not analyze case reports for overall S&P analysis.

Note: All time points are periprocedural

NR: Not reported

Table 5.3.-8: Rates of Safety and Performance Outcome Measures Reported from Subject Devices Analysis – Non-Vascular

	Safety		Performance			
Reference	Tissue Damage puncture of non-intended organs n/N (%)		Infection n/N (%)	Technical Success n/N (%)	Procedural Success n/N (%)	
Teoh et al., 2016 ¹²⁷	0/59 (0%)	0/59 (0%)	1/59 (1.7%)	59/59 (100%)	59/59 (100%)	
Overall Range	0%	0%	1.7%	100%	100%	
Acceptance Criteria	Less than 3.12%	Less than 3.2%	Less than 9.1%	Greater than 77.1%	Greater than 87.1%	
All Datasets Meet Acceptance Criteria (Yes/No)	Datasets Meet Acceptance Criteria Ves		Yes	Yes	Yes	

Note: All time points are periprocedural



SSCP-0008: Worker Guidewires

Revision: C

Argon Location: All Sites

Conclusions of the Clinical Literature Review

A total of 147 articles were identified in the subject device literature search conducted all years until 31 July 2022 with 3 articles being included after the literature review. Of these 3 studies, 2 were related to the peripheral vasculature, and 1 was within the non-vascular indication. However, one of the studies related to the peripheral vasculature was not considered for overall range as case reports are not analyzed for overall safety and performance analysis. There were no articles included that represent the coronary vasculature application. J-tip Teflon guidewire, POINTER nitinol guidewire, and Amplatz guidewire were each reported. Overall, the literature safety and performance analysis included 24 patients with J-tip Teflon guidewire indicated for vertebral angiography and stenting/carotid artery angiography, and 59 patients with Amplatz guidewire indicated for ACC. Performance and safety outcomes with currently available devices, established from the current knowledge/sate of art in the fields and from a review of published literature on competitor devices used to define acceptance criteria and were compared to the rates reported in the literature. The analysis of safety objectives demonstrated consistent clinical outcomes with the current acceptance criteria rates with 100% technical and procedural success rates with no unanticipated adverse events observed. The safety and performance objectives reported from the subject device literature search analysis met the predefined acceptance criteria, therefore, suggesting the subject devices continue as standard of care devices.

5.4. An overall summary of the clinical performance and safety

The Guidewire Families demonstrated well known safety and clinical performance using robust SOA with clinical guidelines from the SOA calling the devices standard of care with bench studies and biocompatibility testing providing evidence that the Guidewire Families are standard of care devices. The Guidewire Families are used as ancillary devices in well-established procedures in the vasculature (central / peripheral) and in non-vascular applications. The use of guidewires during the procedure reflects the current standard of care. The Guidewire Families incorporate technical characteristics that are common to guidewires and have well established clinical performance and safety characteristics in vascular and non-vascular use. Multiple configurations and differences in material are available to provide specific characteristics required in these procedures. Based on the simplicity and conservation of the overall design of guidewires, and similarity of performance requirements across similar clinical applications, benchtop testing standards may apply to multiple guidewires in scope. Therefore, the outcomes of benchtop testing may support performance characteristics of guidewires within the group sharing the same technical or performance requirements. Similarly, biocompatibility assessments can support guidewires sharing the same materials and used in similar applications, e.g., vascular.

In conclusion, it has been shown that the Guidewire Families are established standard of care devices with similarities between them that do not affect the safety or performance of the devices.

CAQ-QA-025-F1 Rev F: Summary of Safety and Clinical Performance (SSCP)

Page 24 of 32



SSCP-0008: Worker Guidewires

Revision: C

Argon Location: All Sites

Benefit / Risk Assessment

The benefits and risks of the Guidewire Families are discussed in CER-001 Rev E. As it was objectively demonstrated that clinical data on the subject devices demonstrate that the subject devices are safe and perform as intended when used according to their IFUs, therefore, continue to be standard of care devices that are essential for assisting catheter devices during diagnostic and intervention procedures.

Based on the review of the current knowledge/SOA, the clinical outcome parameters relevant to examine clinical safety and performance of the Guidewire Families were identified in Table 5.4.-1 & Table 5.4.-2 below.

Table 5.4.-1: The Guidewire Families Safety and Performance Objectives Identified from Clinical Data Sources – Peripheral Vascular

Chinear Data Sources Tempherar vascular			
Outcome	Subject Device Clinical Literature %	Safety and Performance Acceptance Criteria %	All data sets meet acceptance criteria?
Safety			
Vessel perforation	0%	Less than 2.4%	Yes
Vessel dissection	0%	Less than 2.9%	Yes
Thrombus/occlusion	0%	Less than 1.9%	Yes
Performance		·	·
Technical success	100%	Greater than 81.8%	Yes
Procedural success	100%	Greater than 83.3%	Yes

Note: All time points are periprocedural



SSCP-0008: Worker Guidewires

Revision: C

Argon Location: All Sites

Table 5.4.-2: The Guidewire Families Safety and Performance Objectives Identified from – Non-Vascular

Outcome	Subject Device Clinical Literature %	Safety and Performance Acceptance Criteria %	All data sets meet acceptance criteria?
Safety			
Tissue damage	0%	Less than 3.12%	Yes
Perforation or puncture of non-intended organs	0%	Less than 3.2%	Yes
Infection	1.7%	Less than 9.1%	Yes
Performance			
Technical success	100%	Greater than 77.1%	Yes
Procedural success	100%	Greater than 87.1%	Yes

Note: All time points are periprocedural

As standard of care devices, a lower level of clinical evidence for the Guidewire Families can be justified to be sufficient for the confirmation of conformity with relevant GSPRs. The clinical data was further evaluated to demonstrate sufficient clinical evidence in support of conformity to the GSPRs with an assessment per MDCG 2020-6. Table 5.4.-3 summarizes the ranking of each data set.

Clinical evidence demonstrating the safety and performance of Class III devices (Guidewire Families) consists of scientific literature (Rank 4 and 6), proactive PMS data – customer survey data (Rank 8), complaint data (Rank 7) and bench testing (Rank 12). This meets the recommendation of demonstrating sufficient clinical evidence for Class III devices.

Therefore, there are sufficient data sets to support the safety and performance of the Guidewire Families as standard of care devices.

Table 5.4.-3: Clinical Evidence Supporting Guidewire Families

Data Source	Device / Quantity	Rank per MDCG 2020-6
State of the Art	Evaluation of state of the art, including evaluation of clinical data from competitor devices	6
Proactive PMS data Customer Survey Data	Worker Guidewire Product Family-33 surveys Worker Guidewires-53 surveys	8
Literature Articles (n=2) Outcomes from studies with potential methodological flaws but where data can still be quantified, and acceptability justified	J-tip Teflon guide wire, 24 patients Amplatz guidewire, 59 patients	4

CAQ-QA-025-F1 Rev F: Summary of Safety and Clinical Performance (SSCP)



\$SCP-0008: Worker Guidewires

Revision: C

Argon Location: All Sites

Literature Articles (n=1) Individual case reports on the subject device	POINTER nitinol guide wire, 1 patient	9
	Guidewires - 1,406,760 complaints Worker Guidewires - 142,514 complaints	7
Complaint Data and vigilance data	Lunderquist Stainless Steel Guidewires, WORKER Guidewires, POINTER Nitinol Guidewires, Access Guidewires - 46,108 complaints	7
Bench Testing	Mechanical testing for strength and endurance, biological safety, usability	12

Clinical Benefits/Performance Analysis

Clinical benefits encompass any claims about clinical safety and performance outcomes and include the ability of the Guidewire Families to achieve their intended purpose as claimed. As a clinical benefit, the subject devices may provide percutaneous placement of intravascular or non-vascular devices during diagnostic and interventional procedures. Therefore, the clinical benefits of the Guidewire Families have been substantiated based on objective evidence from the appraised data— either clinical, non-clinical, or both.

Clinical Risks and Safety Analysis

The risk management process is conducted according to procedures defined in CAQ-QA-013. Risk Management in accordance with principles of ISO14971: 2019 Medical devices — Application of Risk Management to Medical Devices.

The Guidewire Families are reviewed for risk and undergo a failure modes and effects analysis (FMEA) and/or Hazard Analysis. Risk assessment reports are reviewed at defined time intervals and updated based on data from literature and commercial complaints.

5.5. Ongoing or planned post-market clinical follow-up.

As documented in the PMS plan (PMSP-0008), PMCF is a key subset of the PMS and shall have its own governing plan (PMCFP-0027). The primary objectives of these PMCF plans are to specify the methods and procedures for proactively collecting and evaluating clinical data to support the safety and performance of Guidewire Families and continuously gain knowledge of use related to:

- Confirm the safety and performance throughout the expected lifetime of the Guidewire Families by ensuring compliance of the device to the GSPRs.
- Previously unknown side effects
- Side effects and contraindications
- New or emergent risks, based on factual evidence.



SSCP-0008: Worker Guidewires

Revision: C

Argon Location: All Sites

Argon will conduct the following activities in the post-market, including general and specific methods/procedures, for the Class III guidewires. A summary table of the different PMCF activities foreseen by the manufacturer is provided below:

Activity ID	Description of activity	Aim of the activity	Rationale and known limitations of the activity	Timelines
1	General: Scientific Literature Review	☐ Confirm the safety and performance of the subject devices. ☐ Ensure the continued acceptability of the benefit-risk ratio. ☐ Identify possible systematic misuse or off-label use	Allows evaluation of information on current knowledge and state of the art. Limitations: Clinical data limited to published data from literature	Annual review within the calendar year
2	General: Complaint Trending and Analysis	☐ Confirming the safety of the medical device ☐ Identifying previously unknown side-effects (related to the procedures or to the medical devices). ☐ Monitoring the identified side-effects and contraindications	All complaints related to marketed product are captured in our QMS from clinician users and/or distributors of the subject devices. Limitations: Without knowing the sales volumes of the similar devices, it may be difficult to compare the adverse event occurrence rates, but the overall numbers of events and the types of events can be compared.	Annual review within the calendar year
3	Specific: PMCF study to obtain real world data on the use of guidewires in the coronary vasculature, peripheral vasculature, and non-vascular applications.	☐ Confirm safety and performance. ☐ Identify previously unknown side-effects and monitor the identified side effects and contraindications	Observational study intended to collect quantitative data regarding performance of the subject devices for each indication. Limitations: Data quality and availability	Study will be executed within the certification period of the devices up to renewal (2023-2028).



SSCP-0008: Worker Guidewires

Revision: C

Argon Location: All Sites

6. Possible Diagnostic or Therapeutic Alternatives

The alternative to the use of Guidewires is traditional open surgery and inserting catheters blindly. But the emergence of the medical guidewire enabled accurate placement of therapeutic device or access to target lesions decreased medical cost burden and improved treatment efficiency. Guidewires may be best positioned when tracked by fluoroscopy.

7. Suggested profile and training for users

These devices are intended to be used by trained medical personnel in a clinical setting.

8. Harmonized Standards / Common Specifications

Argon Compliance Date/Version	Standards Title		
Labelling			
BS EN ISO 15223-	Medical devices - Symbols to be used with medical device		
1:2021	labels, labelling and information to be supplied - Part 1: General requirements		
EN ISO 20417:2021	Terminology, Symbols and Information Provided with Medical Devices:		
	Information Supplied by the Manufacturer with Medical Devices		
	General Standards – Sterilization		
BS EN ISO 11070:2014/A1:2018	Sterile, single-use intravascular catheter introducers, guidewires and dilators		
ISO 10555-1:2013	Intravascular catheters Sterile and single-use catheters Part 1: General requirements		
BS EN 556-1:2001	Sterilization of medical devices. Requirements for medical devices to be designated STERILE. Requirements for terminally sterilized medical devices		
BS EN 1422:2014	Sterilizers for medical purposes - Ethylene oxide sterilizers - Requirements and test methods		
EN ISO 11135:2019	Sterilization of health care products - Ethylene oxide - Part 1: Requirements for development, validation and routine control of a sterilization process for medical devices		
AAMI TIR28:2016	Product Adoption and Process Equivalence for Ethylene Oxide Sterilization		
EN ISO 14644-	Classification of Air Cleanliness, Clean rooms & Associated Controlled		
1:2015	Environments. Part 1: Classification of air cleanliness		
EN ISO 14644-	Cleanrooms and associated controlled environments - Part 2: Monitoring to provide		
2:2015	evidence of cleanroom		
	performance related to air cleanliness by particle		
	concentration		
BS EN ISO 11737-	Sterilization of medical devices - Microbiological methods - Part 1: Determination		
1:2018	of a population of microorganisms on products		



Summary Of Safety and Clinical Performance (SSCP) SSCP-0008: Worker Guidewires

Revision: C

Argon Location: All Sites

Argon Compliance Date/Version	Standards Title		
BS EN ISO 10993- 7:2022	Biological evaluation of medical devices. Ethylene oxide sterilization residuals		
NSI/AAMI ST72:2019	Bacterial Endotoxins Test		
	General Standards – Quality Systems		
EN ISO 13485:2016	Medical devices. Quality management systems. Requirements for regulatory purposes		
	Risk Management		
EN ISO 14971:2019	Medical Devices - Application of Risk Management to Medical Devices		
	Biological Safety		
BS EN ISO 10993- 1:2020 + LC:2021	Biological Evaluation of Medical Devices – Part 1: Evaluation and testing		
BS EN ISO 10993- 3:2014	Biological evaluation of medical devices Part 3: Tests for genotoxicity, carcinogenicity and reproductive toxicity		
BS EN ISO 10993- 4:2017	Biological evaluation of medical devices Part 4: Selection of tests for interactions with blood		
BS EN ISO 10993- 5:2009	Biological evaluation of medical devices Part 5: Tests for in vitro cytotoxicity		
BS EN ISO 10993- 10:2013	Biological evaluation of medical devices Part 10: Tests for irritation and skin sensitization		
BS EN ISO 10993- 11:2018	Biological evaluation of medical devices Part 11: Tests for systemic toxicity		
BS EN ISO 10993- 12:2021	Biological Evaluation of Medical Devices – Part 12: Sample preparation and reference materials		
BS EN ISO 10993- 18:2020	Biological evaluation of medical devices — Part 19: Physico-chemical, morphological and topographical characterization of materials		
BS EN ISO 10993- 19:2020	Standard Guide for Biocompatibility of Medical Device Packaging Materials		
	Clinical Evaluation		
MEDDEV 2.7/1 Rev4	Clinical evaluation: Guide for manufacturers and notified bodies		
Design Control			
EN ISO 14971	Medical devices - Application of risk management to medical devices		
Usability			
IEC 62366-1:2015 & IEC 62366-1:2015/COR1:2016	Medical Devices – Application of usability engineering to medical devices		
Packaging			
EN ISO 11607- 1:2020	Packaging for Terminally Sterilized Medical Devices. Part 1: Requirements for materials, sterile barrier systems, and packaging systems.		



Summary Of Safety and Clinical Performance (SSCP) SSCP-0008: Worker Guidewires

Revision: C

Argon Location: All Sites

Argon Compliance	Standards Title	
Date/Version		
EN ISO 11607-	Packaging for Terminally Sterilized Medical Devices. Part 2: Validation	
2:2020	requirements for forming, sealing and assembly processes	
EN ISO 2233:2001	Packaging Complete, filled transport packages and unit loads Conditioning for testing	
ASTM D4169 :2022	Standard Practice for Performance Testing of Shipping Containers and Systems -	
ASTM F2096 –	Standard Test Method for Detecting Gross Leaks in	
2011 (R2019)	Medical Packaging by Internal Pressurization (Bubble Test)	
	- ASTM F 2096-11 (2019)	
ASTM F1929 - 15	Standard Test Method for Detecting Seal Leaks in porous	
	Medical Packaging by Dye Penetration - ASTM F 1929	
ASTM F88 / F88M -	Standard Test Method for Seal Strength of Flexible Barrier Materials - ASTM F88	
2021		
ASTM F1980 - 2021	Standard Guide for Accelerated Aging of Sterile Barrier Systems for Medical	
	Devices - ASTM F1980	
Post Market Clinical Follow-Up		
MEDDEV 2.12/2	Post Market Clinical Follow-up studies	
Rev2		
Vigilance		
MEDDEV 2.12/1	Guidelines on a Medical Devices Vigilance System	
Rev8		

9. Revision History

Revision	Date Issued	Change Description	Revision validated by the Notified Body?
A	27 July, 2023	Initial Report	☐ Yes Validation language: English ☐ No (only applicable for class IIa or some IIb implantable devices for which the SSCP is not yet validated by the NB)
В	19 February, 2024	Harmonize the device name and Intended Purpose per the Declaration of Conformity	▼ Yes Validation language: English
С	01 November, 2024	Updating BSI approved IFU numbers and revision numbers, there is no content update.	Not required as content of the SSCP is not being updated.



Summary Of Safety and Clinical Performance (SSCP) SSCP-0008: Worker Guidewires Revision: C

Argon Location: All Sites